

Stainless Steel Braided Water Connectors for Dishwashers

EF-DC SERIES

Flexible braided connectors for dishwasher installations, designed to reduce vibration and withstand pressure surges. Stainless steel braided with reinforced PVC for durability. Available with multiple connection options. Lead-free certified.



FEATURES

- Durable, flexible connector with reinforced PVC core and stainless steel braid.
- Corrosion-resistant chrome-plated brass nuts.
- Secure crimped nut-to-hose connection.
- EPDM washer ensures a safe, watertight seal.

MATERIALS

Braided Jacket	Stainless Steel 304 (ASTM A240)
Inner Hose	Reinforced PVC
Fittings	Chrome-Plated Brass
Washer	EPDM
Ferrule	Zinc-Plated Steel
Elbow	Brass

CERTIFICATIONS & APPROVALS

- cUPC / NSF 61 compliant for potable water
- NSF 372 certified lead-free
- ASME A112.18.6-2009 / CSA B125.6-2009



SPECIFICATIONS

Max. Working Temperature	180°F (82°C)
Max. Working Pressure	125 psi (8.6 bar)

JOB NAME:

ENGINEER / ARCHITECT:

JOB LOCATION:

WHOLESALE:

SUBMITTAL DATE:

CONTRACTOR:

PRODUCT LINEUP

PART #	DESCRIPTION	LENGTH	QTY/BOX
EF-DC-38C38C-48	Stainless Steel Braided Dishwasher Connector 3/8" Compression x 3/8" Compression	48"	50
EF-DC-38C38C-60		60"	50
EF-DC-38C38C-72		72"	50
EF-DC-38C38L-48	Stainless Steel Braided Dishwasher Connector 3/8" Compression x 3/8" Elbow	48"	50
EF-DC-38C38L-60		60"	50
EF-DC-38C38L-72		72"	50
EF-DC-38C38L-96		96"	50
EF-DC-12C38L-60	Stainless Steel Braided Dishwasher Connector 1/2" Compression x 3/8" Elbow	60"	50
EF-DC-38CHBL-48	Stainless Steel Braided Dishwasher Connector 3/8" Compression x 3/8" Compression	48"	50
EF-DC-38CHBL-60		60"	50
EF-DC-38CHBL-72		72"	50
EF-DC-Kit-48	Stainless Steel Braided Dishwasher Connector 3/8" Compression x 3/8" Compression 1/2" C, 3/8" EL, 3/4 HB Adapters	48"	50
EF-DC-Kit-60		60"	50
EF-DC-Kit-72		72"	50