

Stainless Steel Braided Water Connectors for Faucets

EF-FC SERIES

Flexible connectors for faucet installations, designed to reduce vibration and handle pressure surges. Stainless steel braided with reinforced PVC for durability. Available in multiple connection options. Lead-free certified.



FEATURES

- Durable, flexible connector with reinforced PVC hose and stainless steel braid.
- Chrome-plated brass nuts for corrosion resistance.
- Secure nut-to-hose connection with pneumatic crimp.
- EPDM washer ensures a safe, watertight seal.

MATERIALS

Braided Jacket	Stainless Steel 304 (ASTM A240)
Inner Hose	Reinforced PVC
Fittings	Chrome-Plated Brass
Washer	EPDM
Ferrule	Zinc-Plated Steel

CERTIFICATIONS & APPROVALS

- cUPC / NSF 61 compliant for drinking water
- NSF 372 certified lead-free
- ASME A112.18.6-2009 / CSA B125.6-2009



SPECIFICATIONS

Max. Working Temperature	180°F (82°C)
Max. Working Pressure	125 psi (8.6 bar)

JOB NAME:

ENGINEER / ARCHITECT:

JOB LOCATION:

WHOLESALE:

SUBMITTAL DATE:

CONTRACTOR:

PRODUCT LINEUP

PART #	DESCRIPTION	LENGTH	QTY/BOX
EF-FC-12F12F-12	Stainless Steel Braided Faucet Connector 1/2" FIP x 1/2" FIP	12"	50
EF-FC-12F12F-16		16"	50
EF-FC-12F12F-20		20"	50
EF-FC-12F12F-24		24"	50
EF-FC-12F12F-30		30"	50
EF-FC-12C12F-12	Stainless Steel Braided Faucet Connector 1/2" Compression x 1/2" FIP	12"	50
EF-FC-12C12F-16		16"	50
EF-FC-12C12F-20		20"	50
EF-FC-38C38C-12	Stainless Steel Braided Faucet Connector 3/8" Compression x 3/8" Compression	12"	50
EF-FC-38C38C-16		16"	50
EF-FC-38C38C-20		20"	50
EF-FC-38C38C-24		24"	50
EF-FC-38C38C-30		30"	50
EF-FC-38DT-12	Stainless Steel Braided Faucet Connector 3/8" Compression x 1/2" Delta Type	12"	50
EF-FC-38DT-16		16"	50
EF-FC-38DT-20		20"	50
EF-FC-38C12F-12	Stainless Steel Braided Faucet Connector 3/8" Compression x 1/2" Compression	12"	50
EF-FC-38C12F-16		16"	50
EF-FC-38C12F-20		20"	50
EF-FC-38C12F-24		24"	50
EF-FC-38C12F-30		30"	50