

Frost Free Sillcock

EF-FFSC SERIES

Easyflex Frost Free Sillcock features a built-in vacuum breaker and automatic drain design to help prevent back siphonage and freeze damage. Ideal for residential and commercial outdoor water applications.



FEATURES

- Frost-Free Design
- Built-In Vacuum Breaker
- Automatic Drain Function
- Lead-Free Brass Construction
- Residential & Commercial Applications
- Available in Multiple Lengths

MATERIALS

Body	Lead-Free Brass
Stem	Brass H65
Handwheel	Aluminum Alloy
O-Rings	NBR
Seals	EPDM

SPECIFICATIONS

Connection Type	1/2" MIP x 1/2" SWEAT
Valve Type	Frost Free Sillcock
Available Lengths	4" – 14"
Maximum Working Pressure	125 psi
Maximum Working Temperature	250°F (121°C)
Vacuum Breaker	Integrated
Drain Feature	Automatic Drain

CERTIFICATIONS & APPROVALS

- cUPC • NSF/ANSI 61 & 372 • ASSE 1019
- ASME A112.18.1 • CSA B125.1



JOB NAME:

ENGINEER / ARCHITECT:

JOB LOCATION:

WHOLESALE:

SUBMITTAL DATE:

CONTRACTOR:

PRODUCT LINEUP

PART #	DESCRIPTION	LENGTH	QTY/BOX
EF-FFSC-012MS-04	1/2" MIP x 1/2" SWEAT	4"	24
EF-FFSC-012MS-06		6"	24
EF-FFSC-012MS-08		8"	24
EF-FFSC-012MS-10		10"	24
EF-FFSC-012MS-12		12"	24
EF-FFSC-012MS-14		14"	24

