

Heavy Duty No-Hub Coupling

EF-NHC SERIES

Easyflex Heavy Duty No-Hub Couplings provide enhanced clamp coverage and increased joint strength for demanding DWV applications. Constructed with 300 series stainless steel components and an ASTM C564 compliant gasket for reliable long-term performance.



FEATURES

- Heavy-Duty Wide Shield Design
- Increased Clamp Load Performance
- 304 Stainless Steel Construction
- ASTM C564 Elastomeric Gasket
- 80 in-lbs Torque Rating

MATERIALS

Shield, Clamp Band, Housing	304 Stainless Steel
Screw & Eyelet	304 Stainless Steel
Gasket	ASTM C564 Compliant Elastomeric Compound

SPECIFICATIONS

Clamp Band Size	9/16"
Hex Head Size	5/16" Hex
Tightening Torque	80 in-lbs
Shield Coating	None
Shield Direction	Bi-Directional
Shield Design	Corrugated Pattern
Shield Thickness	0.007"

CERTIFICATIONS & APPROVALS

- CISPI 310
- CISPI 301 Compliant
- ASTM C1540
- ASTM A888
- Complies to ASTM D 412, 2240, 573, 395, 471, 1149 & 624
- IAPMO Certified



PRODUCT LINEUP

PART #	DESCRIPTION	QTY/BOX
EF-NHC-200HD	2" Heavy Duty No-Hub Coupling, 4 Bands	75
EF-NHC-300HD	3" Heavy Duty No-Hub Coupling, 4 Bands	48
EF-NHC-400HD	4" Heavy Duty No-Hub Coupling, 4 Bands	48
EF-NHC-500HD	5" Heavy Duty No-Hub Coupling, 6 Bands	15
EF-NHC-600HD	6" Heavy Duty No-Hub Coupling, 6 Bands	15
EF-NHC-800HD	8" Heavy Duty No-Hub Coupling, 6 Bands	15
EF-NHC-1000HD	10" Heavy Duty No-Hub Coupling, 6 Bands	12
EF-NHC-1200HD	12" Heavy Duty No-Hub Coupling, 6 Bands	8
EF-NHC-1500HD	15" Heavy Duty No-Hub Coupling, 6 Bands	4