

NSF Certified No-Hub Coupling

EF-NHC SERIES

Easyflex NSF Certified No-Hub Couplings are certified to NSF CISPI 310 and comply with ASTM C564 requirements. Identified by the NSF mark, they provide reliable, code-compliant performance for DWV piping applications.



FEATURES

- NSF Certified (CISPI 310)
- 304 Stainless Steel Shield
- Bi-Directional Shield Design
- ASTM C564 Elastomeric Gasket
- Corrosion Resistant

MATERIALS

Shield, Clamp Band, Housing	304 Stainless Steel
Screw & Eyelet	304 Stainless Steel
Gasket	ASTM C564 Compliant Elastomeric Compound

SPECIFICATIONS

Clamp Band Size	9/16"
Hex Head Size	5/16" Hex
Tightening Torque	60 in-lbs
Shield Coating	None
Shield Direction	Bi-Directional
Shield Design	Corrugated Pattern
Shield Thickness	0.007"

CERTIFICATIONS & APPROVALS



- NSF CISPI 310
- CISPI 301 Compliant
- ASTM C1277
- ASTM A888
- Complies to ASTM D 412, 2240, 573, 395, 471, 1149 & 624
- NSF Certified

PRODUCT LINEUP

PART #	DESCRIPTION	QTY/BOX
EF-NHC-112N	1-1/2" NSF No-Hub Coupling, 2 Bands	100
EF-NHC-200N	2" NSF No-Hub Coupling, 2 Bands	100
EF-NHC-300N	3" NSF No-Hub Coupling, 2 Bands	100
EF-NHC-400N	4" NSF No-Hub Coupling, 2 Bands	100
EF-NHC-500N	5" NSF No-Hub Coupling, 4 Bands	30
EF-NHC-600N	6" NSF No-Hub Coupling, 4 Bands	30
EF-NHC-800N	8" NSF No-Hub Coupling, 4 Bands	15
EF-NHC-1000N	10" NSF No-Hub Coupling, 4 Bands	12