

Super Shield No-Hub Coupling

EF-NHC SERIES

Easyflex Super Shield No-Hub Couplings feature a wider clamp band, larger hex head screws, and higher installation torque ratings for maximum sealing performance in demanding DWV applications.



FEATURES

- Extra-Wide Deep Blue Shield
- 3/8" Hex Heavy-Duty Screws
- High Clamp Force Design
- ASTM C564 Elastomeric Gasket
- Enhanced Sealing Performance

MATERIALS

Shield, Clamp Band, Housing	304 Stainless Steel
Screw & Eyelet	304 Stainless Steel
Gasket	ASTM C564 Compliant Elastomeric Compound

SPECIFICATIONS

Clamp Band Size	5/8"
Hex Head Size	3/8" Hex
Tightening Torque	80 in-lbs
Shield Coating	Deep Blue
Shield Direction	Bi-Directional
Shield Design	Corrugated Pattern
Shield Thickness	0.007"

CERTIFICATIONS & APPROVALS

- CISPI 310
- CISPI 301 Compliant
- ASTM C1540
- ASTM A888
- Complies to ASTM D 412, 2240, 573, 395, 471, 1149 & 624
- IAPMO Certified
- CSA Certified
- NSF Certified



PRODUCT LINEUP

PART #	DESCRIPTION	QTY/BOX
EF-NHC-200SS	2" Super Shield No-Hub Coupling, 4 Bands	75
EF-NHC-300SS	3" Super Shield No-Hub Coupling, 4 Bands	48
EF-NHC-400SS	4" Super Shield No-Hub Coupling, 4 Bands	48
EF-NHC-500SS	5" Super Shield No-Hub Coupling, 6 Bands	15
EF-NHC-600SS	6" Super Shield No-Hub Coupling, 6 Bands	15
EF-NHC-800SS	8" Super Shield No-Hub Coupling, 6 Bands	15
EF-NHC-1000SS	10" Super Shield No-Hub Coupling, 6 Bands	10