

Standard & Reducing No-Hub Coupling

EF-NHC SERIES

Easyflex Standard & Reducing No-Hub Couplings provide secure, leak-resistant connections for DWV piping systems. Constructed with 304 series stainless steel components and an ASTM C564 compliant gasket for reliable performance.



FEATURES

- 304 Stainless Steel Construction
- Bi-Directional Shield Design
- Floating Eyelet Design
- ASTM C564 Compliant Gasket
- Corrosion Resistant

MATERIALS

Shield, Clamp Band, Housing	304 Stainless Steel
Screw & Eyelet	304 Stainless Steel
Gasket	ASTM C564 Compliant Elastomeric Compound

SPECIFICATIONS

Clamp Band Size	9/16"
Hex Head Size	5/16" Hex
Tightening Torque	60 in-lbs
Shield Coating	None
Shield Direction	Bi-Directional
Shield Design	Corrugated Pattern
Shield Thickness	0.007"

CERTIFICATIONS & APPROVALS

- CISPI 310 by IAPMO
- CISPI 301 Compliant
- ASTM C1277
- ASTM A888
- Complies to ASTM D 412, 2240, 573, 395, 471, 1149 & 624
- IAPMO Certified
- CSA Certified



Standard & Reducing No-Hub Coupling

PRODUCT LINEUP

PART #	DESCRIPTION	QTY/BOX
EF-NHC-112	1-1/2" Standard No-Hub Coupling, 2 Bands	100
EF-NHC-200	2" Standard No-Hub Coupling, 2 Bands	100
EF-NHC-300	3" Standard No-Hub Coupling, 2 Bands	100
EF-NHC-400	4" Standard No-Hub Coupling, 2 Bands	100
EF-NHC-500	5" Standard No-Hub Coupling, 4 Bands	30
EF-NHC-600	6" Standard No-Hub Coupling, 4 Bands	30
EF-NHC-800	8" Standard No-Hub Coupling, 4 Bands	15
EF-NHC-1000	10" Standard No-Hub Coupling, 4 Bands	12
EF-NHC-1200	12" Standard No-Hub Coupling, 6 Bands	8
EF-NHC-1500	15" Standard No-Hub Coupling, 6 Bands	4

Reducing No-Hub Coupling

PRODUCT LINEUP

PART #	DESCRIPTION	QTY/BOX
EF-NHC-R2112	2"×1-1/2" Reducing No-Hub Coupling, 2 Bands	100
RF-NHC-R3200	3"×2" Reducing No-Hub Coupling, 2 Bands	100
EF-NHC-R4200	4"×3" Reducing No-Hub Coupling, 2 Bands	100
EF-NHC-R4300	4"×3" Reducing No-Hub Coupling, 2 Bands	100