

Standard & Reducing Flexible Coupling

EF-FCP SERIES

Easyflex's Standard and Reducing Flexible Couplings are designed for quickly connecting cast iron and/or plastic underground sewage, drain, waste, and vent piping and providing a leak-proof seal. The gasket is made of elastomeric materials and the 2 compression bands, housing/clamp, and screw are all made of stainless-steel.



FEATURES

- Soft Rubber Gasket Molds to Pipe Surfaces
- Watertight Seal Performance
- Low Expansion & Contraction
- Resistant to Vibration, Chemicals & Fungus
- Stainless Steel Clamp Assembly
- Underground DWV Applications

MATERIALS

Band & Housing	Stainless Steel 300 Series
Screw	5/16" Hex, Stainless Steel 305/304L
Gasket	Elastomeric PVC (ASTM D5926, C1173)

SPECIFICATIONS

Installation Torque	60 in-lbs
Pipe Compatibility	Cast Iron & Plastic
Application	Underground DWV
Coupling Types	Standard & Reducing

CERTIFICATIONS & APPROVALS

- UPC
- CSA B602
- ASTM C1173, D5926 & IAPMO 4933



Standard & Reducing Flexible Coupling

PRODUCT LINEUP

PART #	DESCRIPTION	QTY/BOX
EF-FCP-112	1-1/2" Standard Flexible Coupling, 2 Bands	50
EF-FCP-114	1-1/4" Standard Flexible Coupling, 2 Bands	50
EF-FCP-200	2" Standard Flexible Coupling, 2 Bands	50
EF-FCP-300	3" Standard Flexible Coupling, 2 Bands	30
EF-FCP-400	4" Standard Flexible Coupling, 2 Bands	30
EF-FCP-600	6" Standard Flexible Coupling, 2 Bands	12

Reducing Flexible Coupling

PRODUCT LINEUP

PART #	DESCRIPTION	QTY/BOX
EF-FCP-R112114	1-1/2" to 1-1/4" Reducing Flexible Coupling, 2 Bands	50
EF-FCP-R200112	2" to 1-1/2" Reducing Flexible Coupling, 2 Bands	50
EF-FCP-R300112	3" to 1-1/2" Reducing Flexible Coupling, 2 Bands	50
EF-FCP-R300200	3" to 2" Reducing Flexible Coupling, 2 Bands	30
EF-FCP-R400300	4" to 3" Reducing Flexible Coupling, 2 Bands	30
EF-FCP-R600400	6" to 4" Reducing Flexible Coupling, 2 Bands	12