

Stainless Steel Braided Water Connectors for Washing Machines

EF-WM SERIES

Flexible braided connectors for washing machine installations, designed to reduce vibration and withstand pressure surges. Stainless steel braided with reinforced PVC for durability. Lead-free certified.



FEATURES

- Durable, flexible connector with reinforced PVC core and stainless steel braid.
- Corrosion-resistant chrome-plated brass nuts.
- Secure crimped nut-to-hose connection.
- EPDM washer ensures a safe, watertight seal.

MATERIALS

Braided Jacket	Stainless Steel 304 (ASTM A240)
Inner Hose	Reinforced PVC
Fittings	Chrome-Plated Brass
Washer	EPDM
Ferrule	Zinc-Plated Steel

CERTIFICATIONS & APPROVALS

- NSF 372 compliant, lead-free
- ASME A112.18.6-2009 / CSA B125.6-2009



SPECIFICATIONS

Max. Working Temperature	180°F (82°C)
Max. Working Pressure	125 psi (8.6 bar)

JOB NAME:

ENGINEER / ARCHITECT:

JOB LOCATION:

WHOLESALE:

SUBMITTAL DATE:

CONTRACTOR:

PRODUCT LINEUP

PART #	DESCRIPTION	LENGTH	QTY/BOX
EF-WM-34HB-48	Stainless Steel Braided Washing Machine Connector 3/4" Hose Barb x 3/4" Hose Barb	48"	50
EF-WM-34HB-60		60"	50
EF-WM-34HB-72		72"	50