

Compression x Compression x Compression Supply Stop Valve (DUAL OUTLET)

EFSV SERIES

Easyflex one-handle dual supply stops provide reliable on/off water control for multiple fixtures or appliances. Constructed from chrome-plated lead-free brass, the precision-machined brass ball and PTFE seats ensure smooth, long-lasting operation. High-performance O-rings resist heat and corrosion. Rated for 125 psi / 180°F and 100% leak tested.



FEATURES

- One Handle Controls Two Outlets
- Quarter-Turn Ball Valve Design
- Lead-Free Brass Construction
- PTFE Seats for Smooth Operation
- 100% Leak Tested

SPECIFICATIONS

Type	One Handle Dual Supply Stop
Connection	Compression x Compression x Compression
Operation	Quarter-Turn
Application	Potable Water Systems

MATERIALS

Body & Ball	Chrome-Plated Brass
Stem	Naval Brass
Ball Seat	PTFE
O-Ring	Nitrile Rubber (NBR)
Handle	Zinc

CERTIFICATIONS & APPROVALS

- NSF/ANSI 61 Lead Free
- cUPC Approved



JOB NAME:

ENGINEER / ARCHITECT:

JOB LOCATION:

WHOLESALE:

SUBMITTAL DATE:

CONTRACTOR:

PRODUCT LINEUP

PART #	DESCRIPTION	QTY/BOX
EFSV-DU-58C38C-14C	5/8"OD Comp x 3/8"OD Comp x 1/4"OD Comp, Dual Outlet	20
EFSV-DU-58C38C-38C	5/8"OD Comp x 3/8"OD Comp x 3/8"OD Comp, Dual Outlet	20

PRODUCT DIMENSIONS