

Stainless Steel Corrugated Copper Water Heater Connectors

EFWC-C SERIES

Innovative copper water heater connectors with optimized helical corrugation for enhanced flow, durability, and performance.



FEATURES

- Optimized corrugation for maximum flow
- Built-in dielectric sleeve
- Lead-free certified
- Multiple fitting options available
- EPDM washer
- 100% leak tested

DESIGN CERTIFICATIONS

- ASME A 112.18.6-2009 / CSA B 125.6-2009
- IAPMO / UPC Certified
- NSF 61 Compliant
- NSF 372 Compliant: Lead-Free



MATERIALS

Tubing	Copper
Nut	Chrome-Plated Brass 3771
Gasket	High-Quality EPDM

SPECIFICATIONS

Operation Temperature	-40°F to 180°F (-42°C to 82°C)
Intermittent Impulse Pressure	Up to 180 psig
Operation Pressure	20 to 125 psi (8.6 bar)

JOB NAME:	ENGINEER / ARCHITECT:
JOB LOCATION:	WHOLESALER:
SUBMITTAL DATE:	CONTRACTOR:

PRODUCT LINEUP

PRODUCT	PART #	TUBE ID	FITTINGS	LENGTH	QTY/BOX
	EFWC-034C-1010-12	3/4" ID	3/4" FIP x 3/4" FIP	12	25
	EFWC-034C-1010-15			15	25
	EFWC-034C-1010-18			18	25
	EFWC-034C-1010-24			24	25
	EFWC-034C-1060-12	3/4" ID	3/4" FIP x 3/4" Sweat	12	25
	EFWC-034C-1060-15			15	25
	EFWC-034C-1060-18			18	25
	EFWC-034C-1060-24			24	25