

Commercial Food Service Gas Connectors

EF-FSGC SERIES

COUNTERTOP APPLIANCE GAS CONNECTORS



Countertop appliance gas connectors are designed for compact installations. Made with corrosion-resistant 304 stainless steel, they feature a yellow PVC coating and zinc-plated fittings for durability and reliable performance.

FEATURES

- Braided stainless steel construction
- Durable and flexible design
- Yellow PVC coating for added protection

MATERIALS

Tubing	Braided Stainless Steel Construction
Coating	Yellow PVC
Fittings	Zinc-Plated Steel S45C

CERTIFICATIONS & APPROVALS

- ANSI Z21.24 / CSA 6.10
- ANSI Z21.75 / CSA 6.27



SPECIFICATIONS

Max. Operating Pressure	0.5 psi
-------------------------	---------

CONNECTOR MINIMUM FLOW CAPACITY

Straight Length Capacity (BTU/Hr., 0.64 SpGr., 1,000 BTU per cubic ft. at 0.5" W.C. pressure drop)

Series	OD (ID)	12"	18"	24"	30"	36"	48"	60"	72"
014	3/8"(1/4")	48,000	43,800	40,000	36,400	33,400	28,300	24,900	23,100
038	1/2"(3/8")	102,000	93,100	85,000	77,100	71,100	60,500	53,200	49,100
012	5/8"(1/2")	180,000	164,200	150,000	136,000	125,000	106,000	93,200	86,000
034	1"(3/4")	290,900	290,900	290,900	270,500	255,900	215,900	197,400	173,900

Easyflex Gas Connectors exceed the minimum flow capacity requirements listed above.

JOB NAME:

ENGINEER / ARCHITECT:

JOB LOCATION:

WHOLESALE:

SUBMITTAL DATE:

CONTRACTOR:



TECHNICAL SPECIFICATIONS

PRODUCT LINEUP

COUNTERTOP APPLIANCE GAS CONNECTORS

MODEL #	TUBE OD/ID	FITTINGS	LENGTH	QTY/BOX
EFGC-012-BJC-1010	5/8"OD 1/2"ID	1/2" MIP x 1/2" MIP	24", 36"	20
EFGC-012-BJC-1011		1/2" MIP x 1/2" FIP	24", 36"	20
EFGC-034-BJC-1414	1"OD 3/4"ID	3/4" MIP x 3/4" MIP	36", 60", 72"	20