

Commercial Food Service Gas Connectors

EF-FSGC SERIES



MOVEABLE APPLIANCE GAS CONNECTORS

Movable appliance gas connectors are designed for countertop applications. Made with corrosion-resistant 304 stainless steel, they feature a yellow PVC coating, zinc-plated fittings, and 360° rotational ends for easy installation.

FEATURES

- Braided stainless steel construction
- 360° rotational fittings for easy installation
- Non-flammable yellow PVC coating for added protection

MATERIALS

Tubing	Stainless Steel 304 (ASTM A240)
Coating	Yellow PVC
Fittings	Zinc-Plated Steel S45C

CERTIFICATIONS & APPROVALS

- ANSI Z21.69 / CSA 6.16 – Connectors for Movable Gas Appliances
- NSF/ANSI/CAN 61 Certified – Health Effects



SPECIFICATIONS

Max. Operating Pressure	0.5 psi
-------------------------	---------

CONNECTOR MINIMUM FLOW CAPACITY

Straight Length Capacity (BTU/Hr., 0.64 SpGr., 1,000 BTU per cubic ft. at 0.5" W.C. pressure drop)

Series	OD (ID)	12"	18"	24"	30"	36"	48"	60"	72"
012	5/8"(1/2")	180,000	164,200	150,000	136,000	125,000	106,000	93,200	86,000
034	1"(3/4")	-	-	290,900	270,500	255,900	215,900	197,400	173,900
100	1 1/4"(1")	-	-	581,800	545,200	515,900	442,700	398,900	347,300

Easyflex Gas Connectors exceed the minimum flow capacity requirements listed above.

JOB NAME:

ENGINEER / ARCHITECT:

JOB LOCATION:

WHOLESALE:

SUBMITTAL DATE:

CONTRACTOR:

PRODUCT LINEUP

MOVEABLE APPLIANCE GAS CONNECTORS

MODEL #	TUBE OD/ID	FITTINGS	LENGTH	QTY/BOX
EFGC-012-BJ-1010	5/8"OD 1/2"ID	1/2" MIP x 1/2" MIP	24", 36", 48", 60"	20
EFGC-034-BJ-1414		3/4" MIP x 3/4" MIP	24", 36", 48", 60", 72"	20
EFGC-010-BJ-1616		1" MIP x 1" MIP	24", 36", 48", 60"	20